

VRF Indoor Unit

MIH36T2MN10 – Medium Static Pressure Duct

1-phase, 208/230V, 60Hz



Submittal Data

Job name: _____

Location: _____

Tag: _____

Date: _____



MIH36T2MN10 Features:

- ♦ High efficiency DC fan motor
- ♦ 10-step static pressure control (requires latest generation wired controllers)
- ♦ 7-speed fan control
- ♦ Fresh air intake
- ♦ High-lift drain pump with 47-1/4in. pump head
- ♦ Built-in EXV
- ♦ Flexible installation for the air inlet may be positioned either on the underside or the rear of the unit

Specifications:

Model			MIH36T2MN10
Cooling ¹	Capacity	kW	11.1
		kBtu/h	38
	Power input	W	285
Heating ²	Capacity	kW	12.3
		kBtu/h	42
	Power input	W	285
Air flow rate ³		cfm	1195/1130/1065/1000/934/869/804
External static pressure		in.wg	0.32(0-0.64)
Sound pressure level ⁴		dB(A)	45.9/45/43.6/41.9/40.5/38.8/37.1
Net dimensions ⁵ (W×H×D)		In.	58-7/16×9-5/8×31-7/8
Packed dimensions (W×H×D)		In.	65-3/8×12-13/16×38-3/4
Net/Gross weight		lbs	116.8/142.4
Pipe connections	Liquid/Gas pipe	In.	Φ3/8/Φ5/8
	Drain pipe	In.	OD Φ1
Minimum Circuit Amps (MCA)		A	3.27
Recommended Fuse Size (MFA)		A	15

Notes:

1. Indoor temperature 80°F DB, 67°F WB; outdoor temperature 95°F WB, 75°F DB; equivalent refrigerant piping length 295-1/4in. with zero level difference.
2. Indoor temperature 70°F DB, 60°F WB; outdoor temperature 47°F DB, 43°F WB; equivalent refrigerant piping length 295-1/4in. with zero level difference.
3. Air flow rate are from the highest speed to the lowest speed, total 7 rates for each model.
4. Sound pressure level is from highest level to lowest level, total 7 levels for each model. Sound pressure level is measured 59-1/16in. below the unit in a semi-anechoic chamber.
5. Unit body dimensions given are the largest external dimensions of the unit, including hanger attachments.

Product specifications change from time to time as product improvements and developments are released and may vary from those in this document.



Dimensional Drawing:

Unit (in.)


Product dimensions

Unit: mm(in)


External dimension, air outlet size, and size of fresh air outlet:




Size of return air inlet (back return air mode):



Dimension of pipe and water pipe:



Size of return air inlet (bottom return air mode), and the distance between the lugs:



Capacity (kBtu/h)	A	B	C	D	E	F	G	H	I
kBtu/h ≤ 9	600(23-5/8)	400(15-3/4)	490(19-5/16)	87.5(3-7/16)	165(6-1/2)	506(19-15/16)	645(25-3/8)	3/4-16 UNF	7/16-20 UNF
9 < kBtu/h ≤ 12	800(31-1/2)	600(23-5/8)	690(27-3/16)	220(8-11/16)	134(5-1/4)	706(27-13/16)	845(33-1/4)	7/8-14 UNF	5/8-18 UNF
12 < kBtu/h ≤ 24	1 050(41-5/16)	850(33-7/16)	940(37)	220(8-11/16)	146(5-3/4)	956(37-5/8)	1 095(43-1/8)	7/8-14 UNF	5/8-18 UNF
24 < kBtu/h ≤ 48	1 400(55-1/8)	1 200(47-1/4)	1 290(50-13/16)	220(8-11/16)	213(8-3/8)	1 306(51-7/16)	1 445(56-7/8)	7/8-14 UNF	5/8-18 UNF