

Mini VRF Heat Pump
R454B ATOM X Series

208/230V, 1Ph, 60Hz
Model: MDV-V36WMN10T

Midea Building Technologies Division
Midea Group

Address: Midea Headquarters Building, 6 Midea Avenue, Shunde, Foshan, Guangdong, China
Postal code: 528311
hvac.midea.com /www.midea-group.com / ics.midea.com

Note: Product specifications change from time to time as product improvements and developments are released and may vary from those in this document.

Unit Performance and Data:


Model			MDV-V36WMN10T
Performance (Ducted/Non-Ducted)			
Cooling[1]	Capacity	Btu/h	36000/36000
	Power Input	W	3000/2707
Heating[2]	Capacity	Btu/h	40000/40000
	Power Input	W	3350/2859
AHRI Ratings (Ducted/Non-Ducted)			
EER2[1]		Btu/h/W	12/13.3
SEER2[1]		Btu/h/W	17.8/20
COP2[1]		W/W	3.5/4.1
HSPF2 (Region IV)[2]		Btu/h/W	9.6/10.1
HSPF2 (Region V)[2]		Btu/h/W	7.7/7.5
Electrical Data			
Power supply		V/Ph/Hz	208/230/1/60
MOP		A	30
MCA		A	25
Fan			
Type × Quantity			Propeller × 1
Air Flow Volume		CFM	3255
Fan Motor Running Current		A	1.9
Fan Motor Output		W	215
Compressor			
Type × Quantity			DC inverter × 1
Compressor Rated Load Amps (RLA)		A	16.5
Compressor Refrigerant Oil Type			VG75R
Compressor Refrigerant Oil Charge Volume		L	1.55
Refrigerant Piping			
Connection Pipe	Liquid pipe	in. (mm)	ϕ3/8 (9.52)
	Gas pipe	in. (mm)	ϕ5/8 (15.9)
Max. Equivalent Pipe Length (ODU to IDU)		ft (mm)	328 (100)
Factory Refrigerant Charge		lbs (kg)	6.83 (3.1)
Refrigerant Type			R454B
Dimension/Weight			
Unit Dimensions (W×H×D)		inch (mm)	40-11/16×34×20-9/16 (1033×864×523)
Packed Dimensions (W×H×D)		inch (mm)	44-3/32×40-35/64×22-3/64 (1120×1030×560)
Net Weight		lbs (kg)	216 (98)
Gross Weight		lbs (kg)	250 (113.5)
Other			
Indoor Units	Connection Ratio	%	50~130
	Maximum IDU quantity		5
Sound Pressure Level [3](Cooling/Heating)		dBA	59/61
Ambient temp. operation range	Cooling	°F	5 to 125
	Heating	°F	-22 to 86
Safety Certification			ETL/AHRI
Protection Devices	High Pressure		High pressure switch, High pressure sensor
	Low Pressure		Low pressure sensor
	Compressor		Discharge temp. protection, Over-current protection

Notes:
1. 95°F dry bulb/75°F wet bulb outdoor air temperature and 80°F dry bulb/67°F wet bulb entering indoor coil air;
2. 47°F dry bulb/43°F wet bulb outdoor air temperature and 70°F dry bulb/60°F wet bulb entering indoor coil air;
3. Sound pressure level is measured 1m in front of the unit and 1m above the floor in a semi-anechoic chamber.

Features:


- 3-ton unit, wide operating range.
- Low GWP R454B refrigerant.
- DC inverter compressor for optimal efficiency.
- Arbitrary topology communication, and communication distance up 6562ft
- Automatic refrigerant charging
- Optional R454B refrigerant shut-off device
- Long piping capability.

Dimensions (unit: in (mm))




Installation Space Requirements (unit: in (mm))

Single unit installation



Note: 24 in (610 mm) clearance required on top of unit.

Multiple unit installation top view



Multiple unit installation side view

